

COOL-DOWN GÜSSING

Sustainable cooling concepts for existing buildings using the example of the municipality of Güssing

REAL CORP 2023, 19. Sept. 2023



Cool down Güssing

The graphic features the text 'Cool down Güssing' in large, bold, blue letters. The letter 'o' in 'Cool' is replaced by a white thermometer with a blue liquid level. The letter 'd' in 'down' is replaced by a blue snowflake. The letter 'G' in 'Güssing' is partially obscured by a light blue silhouette of the Güssing town skyline. To the right of the text is a yellow sun icon with radiating lines. The background is a light blue gradient.

Call for proposals: Smart Cities Demo - Living Urban Innovation 2019

Project duration: 42 months (04/20 – 09/23)

Project partners:

- ▶ Güssing Energy Technologies GmbH
- ▶ 4ward Energy Research GmbH
- ▶ Forschung Burgenland GmbH
- ▶ Joke-Systems GmbH
- ▶ O.K. Energie Haus GmbH
- ▶ Reiterer & Scherling GmbH



- ▶ The municipality of Güssing (like many other cities) is **strongly affected** by summer overheating
- ▶ Increased number of hot days → When temperatures are too high, the **quality of living** and working drops significantly
- ▶ Sharp increase in **energy requirements** for room cooling and air conditioning
- ▶ Later cooling measures are **difficult to implement**

Three commercial buildings, three residential buildings and three public buildings were inspected in detail as part of the project

- Guttomat (garage door manufacturer)



Guttomat
Die Tor
Manufaktur



- Vulcolor Naturfarben (produces natural colors for the food industry)

vulcolor
Naturfarben GmbH



- Autohaus Doczekal

auto
DOCZEKAL
MEIN HÄNDLER. MEINE WERKSTATT.



- Detached house Doczekal



- Detached house Scher-Deutsch



- Residential buildings Krottendorf



- BORG Güssing



- Kindergarten




- Fire station



AVOIDANCE OF HEAT INPUT

- ▶ Sun protection
 - ▶ unavailable
 - ▶ not sufficient
 - ▶ used incorrectly



► Detached house


- Wooden frame construction
- Year of construction 2019
- External blinds with servomotors
- Controlled ventilation device



Detached house

- ▶ Variant 1: Partially automated night ventilation
- ▶ Variant 2: Supplementing the controlled ventilation device with a ground heat exchanger
- ▶ Variant 3: Split air conditioning unit 3 kW and PV system 5 kWp

Detached house



Detached house, assessment according to the AHP method

Bewertungskriterium	Priorität	Klimasplitgerät 3 kW + PV 5 kWp		Teilautomatisierte Nachtlüfung		Erdwärmetauscher zur Vorkühlung	
		Rating	Gewicht	Rating	Gewicht	Rating	Gewicht
Ökologische Aspekte	4.3%	3	0.13	5	0.22	3	0.13
Technische Aspekte	5.2%	4	0.21	4	0.21	2	0.10
Herstellungskosten	11.6%	2	0.23	4	0.46	2	0.23
Betriebskosten	17.5%	4	0.70	5	0.88	4	0.70
Kühleffekt	24.1%	5	1.21	3	0.72	3	0.72
Umgebungseinfluss	3.3%	4	0.13	4	0.13	4	0.13
Umsetzungswahrscheinlichkeit	34.0%	4	1.36	5	1.70	3	1.02
Gesamtbewertung	100.0%		3.97		4.32		3.04

AHP-Method (Analytic Hierarchy Process)


- ▶ Multi-criteria decision making method
- ▶ Economic, ecological, technical aspects; cooling effect; environmental influence; probability of implementation

► Air-flowing ground heat exchanger for controlled ventilation


- + cooler air is brought into the building
- + approx. 10 to 15% savings in heating and cooling energy
- - no dehumidification possible
- - Pay attention to hygiene
- - Retrofitting is complex

► 17 m ventilation pipe in the ground


► Air inlet 32.4 °C → outlet 24 °C




- ▶ Partially automated night ventilation
 - ▶ Push notification to your smart phone
 - ▶ manual opening/closing of windows,...



- ▶ Partially automated night ventilation
 - ▶ measurements in summer 2022



- ▶ Why in combination with PV?
 - ▶ Use PV electricity yourself
- ▶ Air conditioning split unit operating times?
 - ▶ 9 a.m. to max. 5 p.m. with your own PV electricity is usually possible
 - ▶ What after?
 - ▶ Timer, or remote operation via APP
 - ▶ or energy manager with "Smart Grid" interface




► Evaluation of air conditioning and PV

	2022	2023
Numbers of days	7	9
Operating hours	17,5 h	16,5 h
Air conditioning power needs	11 kWh	13 kWh
Coverage via PV	82 %	91 %




► Company Guttomat

- Night ventilation via the existing fire smoke ventilation flaps
- 21 flaps
- Wind, rain sensor
- Control with timer and indoor/outdoor temperature sensor
- - depending on the night temperature outside
- - no dehumidification, no active cooling during the day
- + low operating costs, ecological
- + no unpleasant drafts during the day
- + increased employee productivity, reduced risk of accidents





► Guttomat

- Temperature reduction through night ventilation is clearly visible!
- Early: 22 °C instead of 27 °C
- Midday: 27 °C instead of 31 °C



► Adiabatic cooling

- cools efficiently with water
- saves 90% CO2 and 80% operating costs
- Textile air hoses



► Adiabatic cooling

- Simple calculation/simulation of company buildings/halls
- Statements about comfort
- e.g. www.infranorm.com
- https://www.youtube.com/watch?v=p_y4MsHQoI4



Rahmen- / Simulationsparameter	
Interne Wärmelast:	150 kW
Wärmelast solar max.:	17,6 kW bei 36 °C
Wärmelast solar min.:	14,4 kW bei 18 °C
Berechnungsjahr:	2015
Wetterdatenstandort:	Linz
max. Raumluftfeuchte:	65 %
min. Hallentemperatur:	25,0 °C
min. Zulufttemperatur:	18,0 °C
Anzahl Einheiten:	3 Stk.
CO ₂ -Faktor Strom:	0,258 kg/kWh
CO ₂ -Faktor Wasser:	0 kg/m ³
Strompreis:	0,15 €/kWh
Wasserpreis:	2,00 €/m ³
Leitwert Wasser:	500 µS/cm

Berechnete Werte für die adiabate Kühlperiode		
Betrieb (adiabat):	1 939 h/a	
Wasserverbrauch:	567 m ³ /a	1135 €/a
Betriebskosten:	-80 %	-12743 €/a
CO ₂ :	-87 %	-24 to/a
max. Frischluftmenge:	42 000 m ³ /h	
max. rel. Hallenluftfeuchte:	61 %	
Behaglichkeit		
unbehaglich kühl	0 h	0,0%
etwas zu kühl	4 h	0,2%
komfortabel	1 922 h	99,1%
etwas zu warm	10 h	0,5%
unbehaglich warm	0 h	0,0%

► School

- decentralized ventilation unit
- 800 m³/h for night ventilation
- incl. heat recovery for winter




TECHNOLOGIES AND DEMO SITES

East classrooms

without ventilation unit


2,5 to 4,5 K reduction



West classrooms

without ventilation unit

2 to 4 K reduction




TECHNOLOGIES AND DEMO SITES


Kindergarten Güssing - Kinderkrippe - 16. - 18. August



- ▶ Night ventilation via windows
- ▶ tested manually
- ▶ at the moment installation to get motorized



Project website <https://smartcities.at/projects/cool-down-guessing/>



Christian Doczekal
Güssing Energy Technologies GmbH
c.doczekal@get.ac.at
mobile: +4367688112888